Bush Hog® TOUGH RTNR Series Reverse Till Rotary Tillers

BUSH HOG® TOUGH FEATURES

TOUGH #100 Chain Drive
TOUGH Heavy Duty Gearboxes
TOUGH Replaceable Skids
TOUGH High Carbon, Long Life Steel Blades
TOUGH Solid Rotors
TOUGH Anti-Wrap Device To Protect Seals
TOUGH Slip Clutch Is Standard
TOUGH Powder Coat Paint



| MODELS | RTNR60 | RTNR72 | RTNR80 | |
|-----------------------------|--------------------------------------------------|----------------------|----------------------|--|
| Tilling Width | 60 inches | 72 inches | 80 inches | |
| Number of Blades | 28 | 36 | 40 | |
| Tractor HP Range | 40 - 55 PTO | 50 - 65 PTO | 60 - 70 PTO | |
| Type Hitch | Cat. I & II, 3 Point | Cat. I & II, 3 Point | Cat. I & II, 3 Point | |
| Offset | 6 inches | 6 inches | 6 inches | |
| Number of Flanges | 7 | 9 | 10 | |
| Rotor Speed | 238 RPM/540 PTO | 238 RPM/540 PTO | 238 RPM/540 PTO | |
| Type of Blades | C Type | С Туре | С Туре | |
| Power to Rotor Transmission | Chain Drive (#100) Single Speed | | | |
| Depth of Cut | Adjustable - 7 inches, 5 Position Lock Skid Shoe | | | |
| Driveline | Slip Clutch Standard | Slip Clutch Standard | Slip Clutch Standard | |
| Approximate Weight | 714 lbs | 797 lbs | 860 lbs | |
| Warranty | 1 year limited warranty | | | |